



EZ 314

Thermal Receipt Printer

Compatible with ESC/POS
POS Software ready
Ethernet or Wi-Fi
Easy To Use
Fast (12 IPS)
Reliable



Receipt Printing, made simple.

Contact us today!



Ethernet configuration



Wi-Fi configuration

Specifications

Print Method	Direct thermal
Print Speed	300mm/sec
Roll Paper	
Width	79.5+/-0.5mm (print width 72mm)
Diameter	83mm
Thickness	0.06 – 0.08mm
Column Capacity	675 dots/line, 512 dots/line
Line Space	3.75mm (changeable)
Character Size	ANK characters
	A: 12*24 dots, 1.5(W)*3.0(H) mm
	B: 9*17 dots, 3.0(W)*3.0(H) mm
Barcode Type	UPC-A / UPC-E / JAN13 (EAN13) / JAN8 (EAN8) CODABAR / ITF / CODE39 / CODE93 / CODE128, QR code
Power Supply	DC 24V/2.5A
Interface	Serial + USB + LAN, Wi-Fi + USB
Cutter	Auto cutter (Full/Partial)
Reliability	
Print head life	62 mi. (100km)
Auto cutter life	1 million cuts
Working Temperature	32-113 Fahrenheit (0-45 Celsius)
Contrast Humidity	10-80%
Drivers	Windows 7, Vista, XP, 2003, 2000, 9X
Printing Command	Compatible with ESC/POS
Dimension	7.68 l x 6.10 w x 5.83 h in. (195 l x 155 w x 148 h mm)
Weight	5.95 Lbs. / (2.70 kg)
Warranty	Two-year / 20Km



860 College View Dr.
Riverton, WY 82501
1-800-800-6614

For more information, contact Ben Hanson at
307-856-4821 Ext. 335
ben.hanson@pertechindustries.com
Or contact your regional sales representative.